



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

MGA RESEARCH CORPORATION  
 TECHNICAL SERVICES LABORATORY  
 12790 Main Rd.  
 Akron, NY 14001  
 Steven Abramowski Phone: 716 542 5515  
 steve.abramowski@mgaresearch.com  
[www.mgaresearch.com](http://www.mgaresearch.com)

MECHANICAL

Valid To: August 31, 2017

Certificate Number: 1762.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory for the following tests on aerospace, defense, automotive, battery, and any other parts/items using the test methods listed below:

**Test Description**

**Test Method(s)**

Acceleration Testing<sup>1</sup>

Up to 75g constant acceleration  
 Connections during test: electrical / pressure  
 Chamber size: 12' tall x 15.8' x 12.5'  
 36" radius wing

MIL-STD-202G (Method 212),  
 MIL-STD-810A-G (Method 513 Centrifuge);  
 RTCA/DO/160D-F

Altitude Testing<sup>1</sup>

2.92 inches Hg  
 Connections during test: electrical / pressure  
 (Can be conducted in conjunction with  
 Temperature Testing)

MIL-STD-202G (Method 105),  
 MIL-STD-810A-G (Method 520 w/o Vibration at  
 Altitude);  
 RTCA/DO/160D-F (Section 4);  
 ST/SG/ac.10/27/Add.2;  
 United Nations 3090/3091 T1

Charge / Discharge Testing<sup>1</sup>

Battery Forced Discharge Testing  
 Battery Overcharge Test  
 AC Current Measure: (0.01 to 12,000) amps  
 DC Current Measure:(0.01 to 12,000) amps  
 Resistance Measure (Including Insulation)<sup>1</sup>:  
 (100  $\mu\Omega$  to 11 G $\Omega$ )  
 Voltage Measure: (0.0001 to 1000) VDC,  
 (0.0001 to 1000) VAC

ST/SG/ac.10/27/Add.2;  
 United Nations 3090/3091 T7,  
 United Nations 3090/3091 T8;  
 UL 1642, UL 2054;  
 SAE J2464 (Section 4.4.3);  
 MIL-STD-202 Notice 1 (Methods 302 and 303A)

**Test Description**

**Test Method(s)**

**Force Deflection (Tensile / Compression) <sup>1</sup>**

Cylinder Stroke: 12 inches  
Compression Load: 100,000 lbs  
Tension Load: 100,000 lbs

SANDI 2005-3123

**Humidity Testing<sup>1</sup>**

Humidity Range: (10 to 95) % RH  
Temperature Range: (+4 to 93) °C  
Chamber Size (max): 3x3x3 Feet

MIL-STD-202G (Methods 103 and 106),  
MIL-STD-810A-G (Method 507);  
RTCA/DO/160D-F

**Impact**

United Nations 3090/3091 T6;  
ST/SG/ac.10/27/Add.2;  
UL 1642, UL 2054

**Load Fatigue Testing<sup>1</sup>**

Up to 100,000 lbs

GMN 4634P

**Manual Chemical Application**

Label Permanence

UL 2271

**Mass Measure<sup>1</sup>**

(0 to 500) lbs

ST/SG/ac.10/27/Add.2;  
United Nations 3090/3091 T1, T2, T3, T4

**Salt Fog (Corrosion) <sup>1</sup>**

Chamber size (max): 2x3x4 Feet

ASTM B117, ASTM B685,  
ASTM G85 Annex A4;  
IEC 60529; JIS-D-0203, S2;  
MIL-STD-202D (Method 101),  
MIL-STD-810A-G (Method 509);  
RTCA/DO/160D-F

**Shock Testing<sup>1</sup>**

**Mechanical Shock**

Up to 3500g Peak  
Minimum Duration: 0.5 Milliseconds

ST/SG/ac.10/27/Add.2;  
United Nations 3090/3091 T4;  
IST A-1A2001;  
MIL-STD-202D-G (Method 213),  
MIL-STD-810 A-G (Method 516);  
RTCA/DO/160D-F (Section 7)

**Pyrotechnic (Pyro) Shock**

Up to 10,000 g  
Frequency: (20 to 10000) Hz

MIL-STD-202G (Method 213),  
MIL-STD-810 A-G (Procedure VII)

**Short Circuit Testing<sup>1</sup>**

Down to 0.001 circuit resistance

ST/SG/ac.10/27/Add.2;  
United Nations 3090/3091 T5;  
UL 1642, UL 2054;  
SAE J2464 (Sections 4.4.1 and 4.4.2)



**Test Description**

**Test Method(s)**

Temperature Testing<sup>1</sup>

Temperature Measurement Capabilities  
(-190 to +1350) °C

UL 1642, UL 2054

Temperature Testing<sup>1</sup>

Temperature Range: (-70 to +250) °C  
Ramp Rate: 10°C /minute

ST/SG/ac.10/27/Add.2;  
United Nations 3090/3091 T2;  
MIL-STD-202G (Method 108 up to +177°C),  
MIL-STD-810 A-G (Methods 501 and 503);  
NAVMAT-P-9492;  
RTCA/DO/160D-F (Section 4 & 5);  
SAE J2464 (Section 4.3.2)

Remote chamber available  
(Can be conducted in addition to Vacuum  
Testing, Vibration Testing)

Thermal Cycling (Thermal Shock)<sup>1</sup>

Temperature Range: (-70 to +250)°C  
Chamber Size (max): 16"x16"x16"

MIL-STD-202G (Method 107),  
MIL-STD-810 A-G (Method 503);  
NAVMAT-P-9492;  
RTCA/DO/160D-F

Vibration<sup>1</sup>

Random Vibration

Up to 45 Grms  
Frequency: (5 to 4000) Hz  
Peak-Peak: 1 Inch

IST A-1A2001;  
MIL-STD-202G (Method 214),  
MIL-STD-810 A-G (Method 514);  
NAVMAT-P-9492;  
RTCA/DO/160D-F

Sine Vibration

Up to 90g  
Frequency: (5 to 4000) Hz  
Peak-Peak: 1 Inch

MIL-STD-202G (Methods 201, 204, 214),  
MIL-STD-810 A-G (Method 514);  
NAVMAT-P-9492;  
ST/SG/ac.10/27/Add.2 ( Section 38.3.4.2);  
United Nations 3090/3091 T3;  
RTCA/DO/160D- F

Sine on Random Vibration

Up to 45 Grms  
Frequency: (5 to 2000) Hz  
Peak-Peak: 1 Inch

MIL-STD-202G (Methods 201, 204, 214),  
MIL-STD-810 A-G (Method 514);  
NAVMAT-P-9492;  
RTCA/DO/160D-F

Random on Random Vibration

Up to 45 Grms  
Frequency: (5 to 2000) Hz  
Peak to Peak: 1 Inch

MIL-STD-810 A-G (Method 514.4  
Procedure I, Category 8)

(Can be conducted in conjunction with  
Temperature Testing)



**Test Description**

**Test Method(s)**

Multiple Axis Vibration Testing (6 DOF MAST)<sup>1</sup>  
6 Inch Displacement on all Cylinders

MIL-STD-810G (Method 514.6 Procedure II)

Waterproofness  
Drip Test

MIL-STD-810 A-G (Method 506.4)

Water Spray

MIL-STD-810 A-G (Method 506.4);  
SAE J1455

Immersion

MIL-STD-810 A-G (Method 512.4)  
KMVSS 48 (Section 48.6.2)

Drop Test

MIL-STD-810 A-G (Method 516.5)

Crush Testing<sup>1</sup>

Up to 100,000 lbs  
Variable Platens

SAE J2464 (Section 4.2.6)

Nail Penetration<sup>1</sup>

Speed up to 3.25-in/sec  
Variable Nail Diameter

SAE J2464 (Section 4.2.3)

Dielectric Testing<sup>1</sup>

Up to 5,000 VAC

MIL-STD-202 (Method 301)

Roll Over Simulation Testing

SAND2005-3123 (Section 3.5)

Projectile Testing

UL 1642

<sup>1</sup> *These tests meet industry accepted or customer specified methods within the parameters listed*





## Accredited Laboratory

A2LA has accredited

### MGA RESEARCH CORPORATION

Akron, NY

for technical competence in the field of

### Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).



Presented this 29<sup>th</sup> day of May 2015.

A handwritten signature in black ink, appearing to read "L. J. ...", written over a horizontal line.

President and CEO  
For the Accreditation Council  
Certificate Number 1762.01  
Valid to August 31, 2017  
Revised July 31, 2017

*For the types of tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.*