



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

MGA RESEARCH CORPORATION
 TECHNICAL SERVICES LABORATORY
 12790 Main Rd.
 Akron, NY 14001
 Steven Abramowski Phone: 716 542 5515
 steve.abramowski@mgaresearch.com
www.mgaresearch.com

MECHANICAL

Valid To: July 31, 2017

Certificate Number: 1762.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory for the following tests on aerospace, defense, automotive, battery, and any other parts/items using the test methods listed below:

Test Description

Test Method(s)

Acceleration Testing¹

Up to 75g constant acceleration
 Connections during test: electrical / pressure
 Chamber size: 12' tall x 15.8' x 12.5'
 36" radius wing

MIL-STD-202G (Method 212),
 MIL-STD-810A-G (Method 513 Centrifuge);
 RTCA/DO/160D-F

Altitude Testing¹

2.92 inches Hg
 Connections during test: electrical / pressure
 (Can be conducted in conjunction with
 Temperature Testing)

MIL-STD-202G (Method 105),
 MIL-STD-810A-G (Method 520 w/o Vibration
 at Altitude);
 RTCA/DO/160D-F (Section 4);
 ST/SG/ac.10/27/Add.2;
 United Nations 3090/3091 T1

Charge / Discharge Testing¹

Battery Forced Discharge Testing
 Battery Overcharge Test
 AC Current Measure: (0.01 to 12,000) amps
 DC Current Measure:(0.01 to 12,000) amps
 Resistance Measure (Including Insulation)¹:
 (100 μΩ to 11 GΩ)
 Voltage Measure: (0.0001 to 1000) VDC,
 (0.0001 to 1000) VAC

ST/SG/ac.10/27/Add.2;
 United Nations 3090/3091 T7,
 United Nations 3090/3091 T8;
 UL 1642, UL 2054;
 SAE J2464 (Section 4.4.3);
 MIL-STD-202 Notice 1 (Methods 302 and 303A)

Test Description

Test Method(s)

Force Deflection (Tensile / Compression) ¹

Cylinder Stroke: 12 inches
Compression Load: 100,000 lbs
Tension Load: 100,000 lbs

SANDI 2005-3123

Humidity Testing¹

Humidity Range: (10 to 95) % RH
Temperature Range: (+4 to 93) °C
Chamber Size (max): 3x3x3 Feet

MIL-STD-202G (Methods 103 and 106),
MIL-STD-810A-G (Method 507);
RTCA/DO/160D-F

Impact

United Nations 3090/3091 T6;
ST/SG/ac.10/27/Add.2;
UL 1642, UL 2054

Load Fatigue Testing¹

Up to 100,000 lbs

GMN 4634P

Manual Chemical Application

Label Permanence

UL 2271

Mass Measure¹

(0 to 500) lbs

ST/SG/ac.10/27/Add.2;
United Nations 3090/3091 T1, T2, T3, T4

Salt Fog (Corrosion) ¹

Chamber size (max): 2x3x4 Feet

ASTM B117, ASTM B685,
ASTM G85 Annex A4;
IEC 60529; JIS-D-0203, S2;
MIL-STD-202D (Method 101),
MIL-STD-810A-G (Method 509);
RTCA/DO/160D-F

Shock Testing¹

Mechanical Shock

Up to 3500g Peak
Minimum Duration: 0.5 Milliseconds

ST/SG/ac.10/27/Add.2;
United Nations 3090/3091 T4;
IST A-1A2001;
MIL-STD-202D-G (Method 213),
MIL-STD-810 A-G (Method 516);
RTCA/DO/160D-F (Section 7)

Pyrotechnic (Pyro) Shock

Up to 10,000 g
Frequency: (20 to 10000) Hz

MIL-STD-202G (Method 213),
MIL-STD-810 A-G (Procedure VII)

Short Circuit Testing¹

Down to 0.001 circuit resistance

ST/SG/ac.10/27/Add.2;
United Nations 3090/3091 T5;
UL 1642, UL 2054;
SAE J2464 (Sections 4.4.1 and 4.4.2)



Test Description

Test Method(s)

Temperature Testing¹

Temperature Measurement Capabilities
(-190 to +1350) °C

UL 1642, UL 2054

Temperature Testing¹

Temperature Range: (-70 to +250) °C
Ramp Rate: 10°C /minute

ST/SG/ac.10/27/Add.2;
United Nations 3090/3091 T2;
MIL-STD-202G (Method 108 up to +177°C),
MIL-STD-810 A-G (Methods 501 and 503);
NAVMAT-P-9492;
RTCA/DO/160D-F (Section 4 & 5);
SAE J2464 (Section 4.3.2)

Remote chamber available
(Can be conducted in addition to Vacuum
Testing, Vibration Testing)

Thermal Cycling (Thermal Shock)¹

Temperature Range: (-70 to +250)°C
Chamber Size (max): 16"x16"x16"

MIL-STD-202G (Method 107),
MIL-STD-810 A-G (Method 503);
NAVMAT-P-9492;
RTCA/DO/160D-F

Vibration¹

Random Vibration

Up to 45 Grms
Frequency: (5 to 4000) Hz
Peak-Peak: 1 Inch

IST A-1A2001;
MIL-STD-202G (Method 214),
MIL-STD-810 A-G (Method 514);
NAVMAT-P-9492;
RTCA/DO/160D-F

Sine Vibration

Up to 90g
Frequency: (5 to 4000) Hz
Peak-Peak: 1 Inch

MIL-STD-202G (Methods 201, 204, 214),
MIL-STD-810 A-G (Method 514);
NAVMAT-P-9492;
ST/SG/ac.10/27/Add.2 (Section 38.3.4.2);
United Nations 3090/3091 T3;
RTCA/DO/160D- F

Sine on Random Vibration

Up to 45 Grms
Frequency: (5 to 2000) Hz
Peak-Peak: 1 Inch

MIL-STD-202G (Methods 201, 204, 214),
MIL-STD-810 A-G (Method 514);
NAVMAT-P-9492;
RTCA/DO/160D-F

Random on Random Vibration

Up to 45 Grms
Frequency: (5 to 2000) Hz
Peak to Peak: 1 Inch

MIL-STD-810 A-G (Method 514.4
Procedure I, Category 8)

(Can be conducted in conjunction with
Temperature Testing)



Test Description

Test Method(s)

Multiple Axis Vibration Testing (6 DOF MAST)¹
6 Inch Displacement on all Cylinders

MIL-STD-810G (Method 514.6 Procedure II)

Waterproofness
Drip Test

MIL-STD-810 A-G (Method 506.4)

Water Spray

MIL-STD-810 A-G (Method 506.4);
SAE J1455

Immersion

MIL-STD-810 A-G (Method 512.4)
KMOVSS 48 (Section 48.6.2)

Drop Test

MIL-STD-810 A-G (Method 516.5)

Crush Testing¹
Up to 100,000 lbs
Variable Platens

SAE J2464 (Section 4.2.6)

Nail Penetration¹
Speed up to 3.25-in/sec
Variable Nail Diameter

SAE J2464 (Section 4.2.3)

Dielectric Testing¹
Up to 5,000 VAC

MIL-STD-202 (Method 301)

Roll Over Simulation Testing

SAND2005-3123 (Section 3.5)

Projectile Testing

UL 1642

¹ *These tests meet industry accepted or customer specified methods within the parameters listed*





Accredited Laboratory

A2LA has accredited

MGA RESEARCH CORPORATION

Akron, NY

for technical competence in the field of

Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).



Presented this 29th day of May 2015.

A handwritten signature in black ink, appearing to read "L. J. ...", written over a horizontal line.

President and CEO
For the Accreditation Council
Certificate Number 1762.01
Valid to July 31, 2017
Revised March 28, 2017

For the types of tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.